

TemBreak熱動-電磁式ブレーカ電流低減表

形式	40 における 定格電流 (A)	電流低減値			
		50	55	60	65
XS30NB XE50NS XE50NB	3A	2.5A	2.2A	2A	1.6A
	5A	4.2A	3.8A	3.3A	2.7A
XS30NB XE50NS XE50NB XS50CB	10A	8.5A	7.6A	6.7A	5.5A
XS30NB XE50NS XE50NB XS50CB XE100CB	15A	14A	13.5A	13A	12.5A
	20A	19A	18.4A	18A	17A
	30A	29A	28.5A	28A	27.5A
XE50NS XE50NB XS50CB XE100CB	40A	38A	36.5A	36A	34A
	50A	48A	47A	46A	45A
XE100CB	60A	57A	56A	55A	54A
	75A	72A	70A	69A	67A
	100A	96A	94A	92A	90A
XS50NB XE100NS	10A	9.2A	8.5A	8A	7.5A
	15A	13.5A	13A	12A	11A
	20A	19A	18.4A	18A	17A
	30A	28.5A	27.6A	27A	26A
	40A	38A	36.5A	36A	34.5A
	50A	47.5A	46A	45A	43.5A
XE100NS	60A	57A	55A	54A	52A
	75A	72A	70A	69A	67A
	100A	97A	95A	94A	90A
XS100NB	15A	13A	12A	11.5A	10.5A
	20A	18.5A	17.5A	16.5A	15.5A
	30A	28A	27A	26A	24.5A
	40A	35A	33A	30.5A	28A
	50A	46.5A	44A	41.5A	39A
	60A	55.5A	52.5A	49.5A	46.5A
	75A	68A	64.5A	60A	56A
	100A	94A	91A	87A	82A
XE225CS XE225NC XS225NS	125A	115A	110A	103A	97A
	150A	140A	135A	130A	125A
	175A	165A	160A	155A	150A
	200A	180A	172A	160A	150A
	225A	205A	195A	185A	175A
XE400NS XS400CS XS400NS	250A	235A	225A	215A	210A
	300A	275A	260A	250A	240A
	350A	320A	300A	290A	280A
	400A	375A	360A	350A	330A
XE600NS XS600CS XS600NS	500A	470A	450A	435A	420A
	600A	570A	550A	530A	520A
XS800CS XS800NS	700A	658A	630A	595A	560A
	800A	768A	744A	720A	680A